









RT165

35% Rated Operating Capacity	1,650 lbs.
Operating Weight	8,143 lbs.
Horsepower	68.4 hp
Ground Pressure	6.5 / 5.2 psi
Maximum Hinge Pin Height	119.6 in.
Overall Length w/Bucket	126.2 in.
Overall Height	77.5 in.
Overall Width w/Bucket	66 in.

RT185

35% Rated Operating Capacity	1,850 lbs.
Operating Weight	9,140 lbs.
Horsepower	69.9 hp
Ground Pressure	6.6 psi
Maximum Hinge Pin Height	128 in.
Overall Length w/Bucket	144 in.
Overall Height	83 in.
Overall Width w/Bucket	65.9 in.

RT215

2,150 lbs
9,940 lbs
72 h
4.8 ps
128 in
148.1 in
83.1 in
73.9 in

RT255

35% Rated Operating Capacity	2,550 lbs
Operating Weight	11,600 lbs
Horsepower	74.3 h
Ground Pressure	5.3 ps
Maximum Hinge Pin Height	128 in
Overall Length w/Bucket	157.8 ir
Overall Height	83.1 in
Overall Width w/Bucket	83.9 in

VT320

35% Rated Operating Capacity	3,200 lbs.
Operating Weight	11,610 lbs.
Horsepower	114 hp
Ground Pressure	5.3 psi
Maximum Hinge Pin Height	130 in.
Overall Length w/Bucket	159.8 in.
Overall Height	83.1 in.
Overall Width w/Bucket	83.9 in.





ONE GEHL WAY | WEST BEND, WI | 53095

www.gehl.com/PilotApproved





now landed.



the ideal line-up.

he all-new Pilot Series track
loaders from Gehl are the ideal
machines for your equipment fleet.
Now equipped with an all-new
seat-mounted pilot control system and
industry-exclusive features like IdealTrax™
automatic track tensioning and IdealAccess™
fold-up door, the Gehl track loaders are now
leaders in comfort and efficiency.

For equipment owners and operators looking for responsive operation powered by

simple and reliable controls, the Gehl Pilot Series is meant for you. The new pilot control system, similar to the controls of the Gehl skid loader line, gives the operator true 1:1 proportional control over the drive system.

The redesigned cab mounts the controls to the seat, providing added leg room and less arm fatigue during operation.

IdealTrax™ automatic track tensioning system ensures the proper track tensioning when the engine is started. To reduce strain

on the track components, the tension is released when the engine is turned off.

IdealAccess™ fold-up door allows easy entrance and exit from the machine, even when a large attachment is installed. The fold-up door design allows the operator to run the machine with the door folded up for added ventilation.

Find your local dealer at www.gehl.com or visit the website below to get more information on the entire Pilot Series line-up and find your ideal Gehl track loader today!

